Empowered by Innovation

# NEC MultiSync® LCD2190UXi

- Highly innovative LCD monitor with SA-SFT (SuperFine Technology) TFT display
- Ultra-thin frame (14.9 mm)
- L-shape front button technology for intuitive OSD control
- ambix³ ™ Technology – safety of investment with analog/digital interfaces (DVI-I, DVI-D, VGA) with up to 3 inputs simultaneously
- Rapid Response technology 10 ms (grey-to-grey)
- RapidMotion feature guarantees smooth representation of moving images
- TileMatrix and TileComp features
- AutoBright technology
- AmbiBright: Ergonomics and power saving ambient light sensor
- OmniColor™: sRGB and 6-axis-colour-control
- ErgoDesign®: Height adjustable stand (150 mm)
- GammaComp: 12 bit LUT (look up table) and 12 bit gamma correction
- CableComp for best picture quality through automatic signal compensation of long cables and weak signals incl. Sync continuity detection
- ColorComp for best uniformity of brightness and colour
- TORO™ Design: Screen rotation 90° (portrait capability)
- Realtime clock with scheduler
- Low power consumption and EcoModes for reduced Total Cost of Ownership (TCO)

see more.

NEC Display Solutions

# NEC MultiSync® LCD2190UXi

| | |
|---|---|
| Panel Technology | SA-SuperFine (S-IPS) TFT |
| Screen Size [inch/cm] | 21.3/54 |
| Pixel Pitch [mm] | 0.270 |
| Viewing Angle | 178° horizontal / 178° vertical (typ. at contrast ratio 10:1) |
| Contrast Ratio (typ.) | 500:1 |
| Brightness (typ.) [cd/m²] | 250 |
| Response Time (typ.) [ms] | 10 (grey-to-grey), 20 (9 white / black; 11 black / white) |
| Colours [Mio.] | 16.77 |
| Horizontal Frequency [kHz] | 31.5 - 91.1 |
| Vertical Frequency [Hz] | 50.0 - 85.0 |
| Optimum Resolution | 1600 x 1200 at 60 Hz |
| Other Resolutions | 1200 x 1600; 1280 x 1024; 1280 x 960; 1152 x 870; 1152 x 864; 1024 x 768; 832 x 624; 800 x 600; 720 x 400; 640 x 480 |
| Connectors | 3 (Digital: 1 x DVI-D; Digital/ Analog: 1 x DVI-I; Analog: 1 x D-sub 15 pin) |
| Plug & Play | VESA DDC/CI; DDC2B/2Bi; EDID Standard |
| Adjust Functions | Auto Adjust; Colour Temperature Control; Fine Adjust (analog); Sharpness; Brightness; Contrast; Intelligent Power Management; Monitor Information; OmniColor™: sRGB and 6-axis-colour-control; Black Level; Expansion Mode; On-Screen-Manager (OSM) lock-out; Advanced NTAA (Advanced Non-Touch-Auto-Adjustment); Language Select; User Menu; Advanced User Menu; Hotkeys |
| Safety and Ergonomics | CE; TCO'03; TÜV ergonomic approved; TÜV GS; C-tick; GEEA/Energy label; Energy Star; FCC Class B; PCT/Gost; UL/C-UL or CSA; CCC; ISO 13406-2 (pixel failure class II); MPR II/ MPR III; PCBC/B-mark; PSB |
| Power Requirements on Mode [W] | 50 (max.) |
| Power Requirements Power-saving Mode [W] | 1 |
| Power Supply | 100-120 V/220-240 V; 0.68 A/0.29 A; integrated power supply |
| Ambient Temperature (operating) [°C] | 5 to 35 |
| Ambient Humidity (operating) [%] | 30 to 80 |
| VESA Mounting [mm] | 100 x 100 |
| ErgoDesign®: Height Adjustable Stand [mm] | 150 |
| Dimensions (W x H x D) [mm] | 464.8 x 424.8 - 574.8 x 247.3 (Landscape mode) |
| Screen Tilt / Swivel [°] | -5 to +30 / -170 to +170 |
| Bezel Width [mm] | 14.9 (left and right) |
| Cable Management | yes |
| Kensington Lock | yes |
| Weight [kg] | 10.9 |
| Specials | Adjustable power LED (colour and brightness); EcoModes; AmbiBright; AutoBright; Direct Brightness and Contrast; Auto Black Level; Auto Brightness; Auto Contrast; ambix³™; CableComp with Sync Continuity Detection; ColorComp; Rapid Response; RapidMotion; TileMatrix; TileComp; OmniColor™; GammaComp (12 bit look up table) and 12 bit gamma correction; TORO™ Design; DDC-CI; NaViSet® and NaViSet® Administrator compatible; Real time clock with scheduler (Power-On and Power-Off timer); Overdrive; Advanced NTAA (Advanced Non-Touch- Auto-Adjustment); Self diagnostics; Quick release stand and handle |
| Audio Functions | Option: MultiSync® Soundbar 90 |
| Colour Versions | Silver Front Bezel, Light Grey Back Cabinet; Black Front Bezel, Black Back Cabinet |
| Shipping Content | Monitor; Power Cable; Signal Cable DVI-A - VGA; Signal Cable DVI-D - DVI-D; CD-ROM; Sales Office List; User`s Manual |
| Warranty | 3 years warranty incl. backlight |

NaViSet® NaViSet® Administrator ambix³™ TECHNOLOGY TORO Design GammaComp CableComp

LCD2190UXi-UK-03/06

All hardware and software names are brand names and/or registered trademarks of the respective manufacturers. All rights reserved. All specifications are subject to change without notice. March 2006